

Flexible PVC Liner Material

ALECO

E·S·ROBBINS

Ultra-smooth flexible sheet material for tank lining, containment and corrosion control.

- > Lightweight
- > Puncture & Abrasion Resistant
- > Flexible - expands and contracts independently from tank
- > Thicknesses from .050 to .394
- > 36", 48" and 73" widths
- > Standard colors are black and white
- > Custom colors & sizes available

PROPERTY	ASTM TEST METHOD	UNIT	RESULT
Specific Gravity	D-792	grams/cm	1.23
Shore A Hardness, 15 Sec (22°C)	D-2240	----	80
Tensile Break @ Strength	D-638	PSI	1804
Elongation @ Break	D-638	%	322
100% Modulus	D-638	PSI	2680
Tear Resistance	D-1004	lb/in	335
Cold Resistance (Tb)	D-746	C	-38
Flammability (Loi)	D-2863	%	19

- Ultra smooth – no bubbles or lakes
- Normal temperature range from -10° F/-23° C to 150° F/66° C
- Compounded on-site for total quality control

www.aleco.com • email: info@aleco.com

2720 E. Avalon Ave. • Muscle Shoals, AL 35661

Ph / (800) 633-3120 • (256) 248-2402

Fax / (800) 750-9616 • (256) 248-2410

P/N 994217
1117