

# Flexible PVC Liner Material

# ALECO

E·S·ROBBINS

Ultra-smooth flexible sheet material for tank lining, containment and corrosion control.

- > Lightweight
- > Puncture & Abrasion Resistant
- > Flexible - expands and contracts independently from tank
- > Thicknesses from .050 to .394
- > 36", 48" and 72" widths
- > Standard colors are black and white
- > Custom colors & sizes available

PROPERTY	ASTM TEST METHOD	UNIT	RESULT
Specific Gravity	D-792	grams/cm	1.24
Hardness Shore A	D-2240	----	90
Tensile Break @ Strength	D-638	PSI	2942
Elongation @ Break	D-638	%	231
100% Modulus		PSI	2173
Tear Resistance	D-1004	lb/in	365
Cold Temperature Resistance	D-746	C°	-24
Flammability	D-2863	%	19

- Ultra smooth – no bubbles or lakes
- Normal temperature range from -10° F/-23° C to 150° F/66° C
- Compounded on-site for total quality control

[www.aleco.com](http://www.aleco.com) • email: [info@aleco.com](mailto:info@aleco.com)  
2720 E. Avalon Ave. • Muscle Shoals, AL 35661  
Ph / (800) 633-3120 • (256) 248-2402  
Fax / (800) 750-9616 • (256) 248-2410

P/N 994217  
0511