Date:		
ALECO® Quote N	lumber:	
Account Number:		
		IMPACDOR® AL-125-2
Address:		IMPORTANT: Provide measurements using the illustration below.
Purchase Order #: _		
Ship To:Address:		
Address:		
Special Markings/Ir	nstructions:	
Quantity:	Single Bi-Parting	
If single panel, specify hing	ie on: Left Right	
Finished Opening:	w Хн	
SPECIFICATIONS:		
0.063" Anodized Alumi	num	
DOOR SKIN MATERI	IAL:	
063" Thick Satin An	odized Aluminum (Recommended)	
18 Gauge Stainless S	Steel	
DOOR FEATURES &	OPTIONS:	
KICK PLATES:		(Single Left Only) (Single Right Only)
	Kick Plate Height: Maximum Width = Door Width)	Note: Door Frame (shaded portion) not included.
KICK PLATE MATER	IAL:	IMPORTANT! SIGNATURE REQUIRED BEFORE PRODUCTION
Stainless Steel - 18 Gauge	Black ABS 0.063" Aluminum	I have reviewed the specifications and authorize ALECO [®] to begin immediate manufacturing of ImpacDor[®] AL-125-2 . I understand that this product will be custom made to my order
HINGE OPTIONS:	Gravity Hinge (Standard)	specifications and is non-returnable. Approved: Date:
	Spring Assist Hinge	Company Name:
WINDOW SIZE:	8.5" x 11" 9" x 14"	Phone:
EDGE: Formed Lead	ding/Trailing Edge Standard	SPECIAL OPTIONS / NOTES
JAMB CONSTRUCTION	Hinge requires a minimum double 2 x 4 wood jamb.	